


Type B - Fire & Life Safety Products

REL.1460SE Series - Standard Duty Universal Mounting

REL.1460SE - Hinge (Pull Side) Mounting

- Standard REL.1460SE series closer shipped with a standard arm, plastic cover, 24V SE track, track roller and wood & machine screw pack
- Non-sized cylinders (REL.1461) for interior doors to 1220mm
- Adjustable hold open force
- Momentary on/off switch board assembly for testing
- Functions as a full rack & pinion door closer when the hold open is not engaged or when the current is interrupted
- Non-handed
- Requires additional system components. See opposite page for specifications relating to the REL.PS07 transformer
- Universal Sentronic track offers concealed or surface wiring
- Standard or optional custom powder coated finish - Optional plated finish on arm and fasteners



Surface Mounting

For interior fire and smoke barrier doors. Single acting cylinder on door top rail. Exposed arm and track to head frame.

Maximum Opening

Butt hinge template allows 110° with hold open points between 85° and 110° at approximately 3° increments. Optional SEL special long track allows hold open points to 120°.

Consult Relcross for all pivot mounted installations.

Butt Hinges should not exceed 127mm in width.

Reveal should not exceed 3mm for standard arm.

Head Frame minimum 51mm.

Top Rail minimum 64mm (38mm with REL.1460SE-18 plate).


Door Width minimum 711mm for standard SE solution.

Clearance minimum 60mm behind the door for 90° installation.

Standard Finish - US28 powder coated silver.

UK Fire Certification in accordance with EN 1634-1:2000 (timber)
WFR No. 142058 **120 mins.** **BS EN 1154:1997**
Certification applies to both applications.

REL.1460SE - Stop Face (Push Side) Mounting



- Standard REL.1460SE series closer shipped with a standard arm, plastic cover, 24V SE track, track roller and wood & machine screw pack
- Non-sized cylinders (REL.1461) for interior doors to 1220mm
- Adjustable hold open force
- Momentary on/off switch board assembly for testing
- Functions as a full rack & pinion door closer when the hold open is not engaged or when the current is interrupted
- Non-handed
- Requires additional system components. See opposite page for specifications relating to the REL.PS07 transformer
- Universal Sentronic track offers concealed or surface wiring
- Standard or optional custom powder coated finish - Optional plated finish on arm and fasteners

Surface Mounting

For interior fire and smoke barrier doors. Single acting cylinder on door top rail. Exposed arm and track to head frame.

Maximum Opening

Butt hinge template allows 110° with hold open points between 85° and 110° at approximately 3° increments. Optional SEL special long track allows hold open points to 120°.

Consult Relcross for all pivot mounted installations.

Butt Hinges should not exceed 127mm in width.

Auxiliary Stop is recommended at the hold open point - applies to both applications.

Top Rail minimum 102mm (38mm from stop face with REL.1460SE-18PA plate)

Stop Width minimum 32mm for track installation.

Door Width minimum 711mm for standard SE solution.

Standard Finish - US28 powder coated silver.