

# L-Series Mortise Lock

## Features and Benefits

### Strong/Durable

- Fully wrapped heavy gauge steel case protects against door edge attacks
- All metal zinc dichromate plated working parts
- Inside lock case protects electronic components
- 2-piece anti-friction tongue reduces wear and tear
- Outside and inside trim thru-bolted together and through the door

#### Secure

- Break-away spindle prevents unsecured failures and provides easy spindle replacement
- Hub blocking plate protects lock against spindle manipulation
- Spring-loaded fusible link provides fail secure mode in case of fire
- Inside lever applied by screwless shank mounting no exposed trim mount screws

#### Adaptable

- Universal lock case 10 functions in one case
- Floating mounting tabs automatically adjust to fit a beveled door edge
- Field reversible handing without opening lock case
- External spring cages allow for simple trim retrofit
- Locking thumbturn on the inside of door visually shows when the door is locked and unlocked
- Lever rotation in both directions (up & down) for ease of use
- Independent lever rotation

The L-Series locks offer the strength, durability, adaptability and security needed in today's high traffic applications. The L-Series locks are intended for commercial, institutional and industrial use in applications such as schools, hospitals and factories where long life and dependable operation is necessary and a high degree of resistance to physical abuse is preferred.



### Performance Specifications

- ANSI: A156.13 Grade Operational and Security\*
- Underwriters Laboratories: c UL us LISTED 3-hour fire rated

# Vandlgard<sup>®</sup>

The L-Series VandIgard is ideal for areas subject to abuse or anywhere vandalism is likely to be present. Vandlgard prevents damage to internal lock components caused by excessive force from kicking, hitting or standing on the lever to gain access.

It's easy to retrofit standard L-Series locks with Vandlgard using the VandIgard Retrofit Kit and an instructional DVD that shows installation on existing hardware.



Locked lever freely rotates down while remaining securely locked.

# Finishes Available



505/605





Bright Brass Satin Brass 606





Satin Bronze Oil-Rubbed Bronze 612 613





**Bright Chrome** 625

Satin Chrome 626



**Dull Bronze**.

oxidized

616





Bright Brass,

619



**Antique Pewter** 620

Bright Bronze,

611



# **Universal Case**

The L9050 universal case can be transformed into 9 different functions\*. The L9050 can be easily converted into all of these functions, with just a few additional parts. For some functions, additional parts are not necessary.

| ANSI<br>Function | Type Function   | Required<br>Additional Parts                      |
|------------------|---|---|
| F01              | L9010 Passage   | No Additional Parts Required                      |
| F04              | L9050 Office  | No Additional Parts Required                      |
| F05              | L9070 Classroom   | No Additional Parts Required                      |
| F07              | L9080 (no outside lever)<br>Showroom                                | B502-948 & K510-680                               |
| F09              | L9060 Apartment<br>Entrance   | Mortise Cylinder Assembly,<br>B502-948 & K510-680 |
| F31              | L9080 (less outside<br>lever and cylinder)<br>Exit or Communicating | L283-150  |
| F32              | L9071 Classroom<br>Security   | Mortise Cylinder Assembly<br>& L583-153           |
|                  | L9080 (less outside<br>lever) Service                               | B502-948, K510-680<br>& L283-150                  |
|                  | L9080 (less inside trim)<br>Utility                                 | B502-948, K510-680<br>& L283-150                  |
|                  | L9070 (less inside trim)<br>Closet                                  | L283-150  |

## L9050 Transformation Parts



\*See Schlage L-Series Universal Transformation Instructions (Form SC-5049) for detailed instructions

### Schlage

111 Congressional Blvd. Suite 200 Carmel, IN 46032 Tel 800.847.1864 Fax 800.452.0663 www.schlage.com