





PRODUCT FEATURES

- Ultra-secure Direct Mount to door frame for strength and reliability
- Fully sealed for weatherproof and tamper-resistant operations
- Sealed 10 ft. [3.05m] jacketed, stranded conductor cable
- Automatic dual voltage no field adjustment required
- Instant release circuit no residual magnetism
- Noise suppression no interference with sensitive electronics
- Efficient, low power usage
- All ferrous metal surfaces plated for durability and rust resistance
- · MagnaCare Lifetime Replacement No Fault Warranty

PRODUCT OPTIONS

- Flexible mounting options for out-swing doors, in-swing doors and metal or wood doors
- BondSTAT magnetic bond sensor -Patented
- Integrated door position switch
- Universal threaded conduit fitting is 1/2" female - 3/4" male
- Split Strike Plates and Offset Strike Plates available

SPECIFICATIONS

- UL 10C Listed
- CAN4-S104, CAN/ULC-S533 Listed
- ANSI/UL 294 Listed
- ANSI/BHMA 156.23, Grade 1; E08501-1500
- NFPA 101
- · CSFM- California State Fire Marshal Approved
- CE:EN 50091-1, EN61000-6-2
- NFMA: 4X
- IEC: IP66

Holding Force:

1800lbs [816kg]

Dimensions:

Magnalock: 12"L x 1-3/4"D x 3"H Strike: 9"L x 1/2"D x 2-3/4"H

Electrical:

350mA at 12VDC 200mA at 24VDC

Operating Temperature:

-40 to +140F [-40 to +60C] Indoor or Outdoor use

Shipping Weight:

16lbs [7.26kg]

Finishes:

US32D/630 - Satin Stainless Steel


CL - Clear (Dress Cover)

BK - Black (Dress Cover)

ASSA ABLOY, the global leader in door opening solutions

US32/629 - Polished Stainless (Dress Cover)

US03/605 - Polished Brass (Dress Cover)




M82B SERIES **1800lbs Holding Force**

Magnalock® Industrial Strength Hold for **Challenging Indoor/Outdoor Environments**

The M82 electromagnetic lock offers unsurpassed magneticholding strength, durability and ease of maintenance for interior, perimeter and exterior access control applications in high-risk environments. With unsurpassed durability, the M82 will last long after most buildings wear out. Flexible mounting options are available for higher security locations and other environments where extreme forces may be encountered.

>> MODELS		PART # Description
M82B	M82 - MBS	
M82BD	M82 - MBS, DPS	
M82B-SS	M82 - MBS w/ Split Strike	
M82FB	M82 - Face Mount, MBS	
M82FBD	M82 - Face Mount, MBS, DPS	
M82FGB	M82 - Face Mount, Conduit, MBS	
M82FGBD	M82 - Face Mount, Conduit, MBS, DPS	
M82GB	M82 - Conduit, MBS	
M82GBD	M82 - Conduit, MBS, DPS	





DUAL VOLTAGE





