



### **PRODUCT FEATURES**

- For use on any push, pull or swing-through door
- Activates electronic release via DPST 2 Amp rated relay when touched to allow free egress
- Backup push button
- 16 ft. [4.8m] 22AWG 6 conductor cable and armored door cord included
- Automatic dual voltage
  12VDC/24VDC
- MagnaCare Lifetime Replacement
  No Fault Warranty

### **PRODUCT OPTIONS**

- EL- Prefix any model for ElectroLynx<sup>®</sup> ready
- D- Prefix any model for dummy bar with no release function

### SPECIFICATIONS

- ANSI/UL 294 Listed
- CSA-C22.2 No.205 Listed
- CSFM California State Fire Marshal Approved
- MEA- City of New York Approved
- CE: EN 50091-1, EN 61000-6-2 Approved

## **Dimensions:** 5"L x 2-1/8"D x 9"H

Electrical: 40mA at rest; 25mA releasing at 12VDC or 24VDC

**Operating Temperature:** +32 to +110F [0 to +43C]

#### Indoor use only **Shipping Weight:** 3lbs [1.36kg]

Finishes: BK - Black anodized


CL - Clear anodized

**TSH** Touch Sense Handle

# Compact Push or Pull Egress Alternative for Maglock Release

Sized to conceal existing mounting holes, the TSH Touch Sense Handle replaces standard pulls on aluminum doors to allow maglock release for egress. With flexible options, it works equally well on inswing doors or as a push-open device for outswing doors, offering a clean look on aluminum frame glass doors.

» MODELS		PART #   Description
TSH-BK	TSH - Push/Pull, Black Anodized	
TSH-CL	TSH - Push/Pull, Clear Anodized	
DTSH-BK	Dummy TSH Handle - Black Anodized	
DTSH-CL	Dummy TSH Handle - Clear Anodized	
EL-TSH-BK	TSH - Push/Pull, Black Anodized, ElectroLynx	
EL-TSH-CL	TSH - Push/Pull, Clear Anodized, ElectroLynx	







DUAL VOLTAGE



59